



## DECLARATION OF PERFORMANCE

DoP 2014\_IF3RSN402

version 1

1. Unique identification code of the product-type:

**IF3RSN402 1K Neutral Silicone Sealant**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: See product packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Sealant for façade elements : EN-15651-1: F-EXT-INT-CC**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**IFI (a trading division of Rapidrop Global Ltd)  
Rutland Business Park, Newark Road,  
Peterborough, PE1 5WA UK**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3 ; System 3 for reaction to fire**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 15651-1-2012-12**

8. Notification body:

**Internal**

9. Declared performance

| Essential Characteristics                      | Declared performance | Harmonized standard           |
|--|----------------------|-------------------------------|
| Reaction to fire                               | Class E              |                               |
| Release of Chemicals                           | Evaluated            | See product safety data sheet |
| Water Tightness & Air Tightness as determined: |                      |                               |
| Stability under load                           | <3mm                 | EN-15651-1-2012-12            |
| Elongation at break                            | >25%                 | Conditioning A                |
| Volume loss                                    | <45%                 | Mortar M1 with Primer         |
| Durability                                     | NF                   |                               |
|  |                      |                               |
|  |                      |                               |
|  |                      | NF = No failure               |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The manufacturer alone is responsible for preparing the declaration of performance in compliance with the numbers.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'M. Curran', with a horizontal line extending to the right.

Martyn Curran; Director

**June 2014**

Disclaimer : The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, Rapidrop makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.